MSDS FOR FAT PAINT, MANUFACTURED FOR THE FAT PAINT COMPANY BY CLOVERDALE PAINT

MATERIAL SAFETY DATA SHEET 03134 Page 1 PRODUCT NAME: INTERIOR FLAT ACRYLIC LATEX HMIS CODES: H C F R P NEUTRAL BASE **PRODUCT IDENTIFIER:** 03134 1 0 0 B **PRODUCT USE:**General purpose water-based coating.WHMIS INFO:NON-CONTROLLED MANUFACTURER'S NAME: Cloverdale Paint Inc ADDRESS : 6950 King George Boulevard Surrey, BC, **EMERGENCY PHONE** : 613-996-6666 **REVISION DATE :** 7-Sep-16 **INFORMATION PHONE** : 604-596-6261 **ABREVIATIONS** : N/AP - NOT APPLICABLE N/AV - NOT AVAILABLE \_\_\_\_\_ \*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 present. \*\*\* \_\_\_\_\_ BOILING POINT:100 Deg CSPECIFIC GRAVITY (H2O=1):1.39VAPOR DENSITY:Heavier than air.PHYSICAL STATE:LiquiEVAPORATION RATE:Slower than n-Liqui Liquid. Butyl Acetate. COATING V.O.C.: 94 g/l (before thinning) SOLUBILITY IN WATER: Soluble. APPEARANCE AND ODOR: Moderately thick liquid; Sweet, slightly ammoniacal odor. FREEZING POINT: 0 deg C pH: 8.75 Not available. COEFFICIENT OF WATER/OIL DIST: N/AV ODOR THRESHOLD: FLASH POINT: N/AP METHOD USED: N/AP FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/AP UPPER: N/AP EXTINGUISHING MEDIA: Use extinguishing media appropriate to surrounding fire. SPECIAL FIREFIGHTING PROCEDURES Handle as a non-flammable liquid. UNUSUAL FIRE AND EXPLOSION HAZARDS Closed containers may explode when exposed to extreme heat. FLAMMABILITY - T.D.G.R. CLASS: Not regulated. SENSITIVITY TO IMPACT: NO

Page 2

03134

# AUTO-IGNITION TEMPERATURE:

Not available

# SENSITIVITY TO STATIC DISCHARGE: NO

## HAZARDOUS COMBUSTION PRODUCTS:

Not available.

# 

#### CHEMICAL STABILITY: STABLE

**CONDITIONS TO AVOID:** Excessive heat, poor ventilation, corrosive atmospheres, excessive aging.

## INCOMPATIBILITY (MATERIALS TO AVOID)

Alkaline materials, strong acids and oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: NONE KNOWN

## HAZARDOUS POLYMERIZATION:

Will not occur.

#### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Excessive exposure to vapours or spray mists may cause minor irritation to the eyes, nose and throat.

#### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Eye Contact: May cause minor irritation, tearing, redness and blurred vision. Skin Contact: May cause minor irritation.

## SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May dry and defat skin causing cracks, irritation and dermatitis.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE** May cause gastrointestinal irritation, vomiting, nausea and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC) Acute health hazards are as listed above. No chronic health hazards.

SENSITIZING CAPABILITY: NONE KNOWN

# **CARCINOGENICITY: NTP CARCINOGEN:**No **IARC MONOGRAPHS:**No **OSHA REGULATED:**No Not available.

**TERATOGENICITY AND EMBRYOTOXICITY** Not available.

**REPRODUCTIVE TOXICITY** Not available.

## MUTAGENICITY

Not available.

#### TOXICOLOGICALLY SYNERGISTIC PRODUCTS

Page 3

03134

None known.

# MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Anesthesia, respiratory tract irritation, dermatitis, nausea, vomiting.

## ADDITIONAL HEALTH INFORMATION

Not available.

#### 

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Clean up with water before allowing to dry. Sodium Chloride can be sprinkled on the spill, which may coagulate the latex and facilitate cleaning with water. Place coagulated waste in a closed container. Flush area with water.

#### WASTE DISPOSAL METHOD

Reclaim or dispose of through a licensed waste disposal company according to Federal, Provincial and local regulations.

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Storage: Keep from freezing. Store in a well ventilated area out of direct sunlight and away from any source of heat. Handling: Avoid prolonged or repeated inhalation of heated vapours or spray mist. Avoid prolonged or repeated skin contact. Wear adequate personal protective equipment.

OTHER PRECAUTIONS: None known.

#### RESPIRATORY PROTECTION

Not normally required when applying by brush or roller. When spraying, wear a mist/dust particulate respirator. In cases of poor or no ventilation, wear a respirator NIOSH approved for organic vapours and particulates.

#### VENTILATION

General (dilution) ventilation is required during use. Local exhaust ventilation is required during operations where this material is heated.

# PROTECTIVE GLOVES

Rubber.

## EYE PROTECTION

Chemical safety glasses, goggles or face shield.

#### OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Use impermeable aprons and protective clothing whenever possible to prevent skin contact.

#### WORK/HYGIENIC PRACTICES

Eye washes and safety showers in the workplace are recommended.

#### 

**INHALATION OVEREXPOSURE:** Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention.

EYE CONTACT: Flush with water for at least 15 minutes. Seek medical attention.

SKIN CONTACT: Wash thoroughly with mild soap and water.

# MATERIAL SAFETY DATA SHEET

03134

## Page 4

**INGESTION:** Drink 1 or 2 glasses of water to dilute. Contact a physician immediately.

**PREPARED BY:** TECHNICAL DEPARTMENT

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Cloverdale Paint Inc. to be accurate. No warranty concerning the accuracy of these sources is made and Cloverdale Paint Inc. will not be held liable for claims relating to use of this information or recommendations.